

# IN MEMORIUM: John Field



Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>FEB 2010</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-2010 to 00-00-2010</b>	
4. TITLE AND SUBTITLE <b>Demonstration of a Retrofit Corrosion-Resistant Fire Hydrant Which Also Protects Against Deliberate Contamination of Critical Army Water Supplies</b>			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>U.S. Army Engineer Research and Development Center (ERDC),Construction Engineering Research Laboratory (CERL),PO Box 9005,Champaign,IL,61822</b>			8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>63</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

# 2010 U.S. Army Corrosion Summit

## February 9-11, 2010


### DEMONSTRATION OF A RETROFIT CORROSION-RESISTANT FIRE HYDRANT WHICH ALSO PROTECTS AGAINST DELIBERATE CONTAMINATION OF CRITICAL ARMY WATER SUPPLIES

Vincent F. Hock, Vicki Van Blaricum, Mark Ginsberg,  
Susan A. Drozd and Eddy Dean Smith, Ph.D., DEE

**Engineer Research and Development Center**  
**Construction Engineering Research Lab**  
Champaign, IL



US Army Corps of Engineers  
**BUILDING STRONG®**




# OSD Corrosion Control Program

- Congressional Directive to DoD
  - ▶ Public Law 107-314, December 2002 Sec: 1067: Prevention and mitigation of corrosion of military equipment and infrastructure
- Tri-Service in nature
- Army facilities projects are co-funded with ACSIM-IMA
- We greatly appreciate their sponsorship, visibility, and support












# Threats and Vulnerabilities





# ***ASCE 2009 Report Card for America's Infrastructure***

- Drinking Water : D-



**Tuberculation in 6-inch Unlined Water Main**





36 Inch Main Break



# ***Degradation Of Water Quality In The Distribution System Can Result In Undetected Localized Corrosion Problems***

**Treatment plant**



**“Old”  
water**



**“Old”  
water**



- Corrosion inhibitors and disinfectants are consumed
- Residence time controlled by system hydraulics
- Remote and low-use areas are especially problematic



# ***EXTENT AND MAGNITUDE OF THE CORROSION PROBLEM***

- Potable Water Distribution System: 880,000 miles of pipe comprise the nation's drinking water distribution network [AWWA WATER\STATS2002].
- Millions of fire hydrants are associated with the network.





If the condition of a pipeline is unknown, or if insufficient data is available to make an accurate assessment of the pipeline condition, then managers cannot be situationally aware and make sound decisions related to:

- Rehabilitation
- Replacement funding
- Schedules
- Priorities for these assets




# Monitoring at an Army Installation








# *Best Approach is a Network Approach Not a choice of just one, or two instruments*





# Corrosion Rate Sensor



- Measures linear polarization resistance (LPR) or electrical resistance (ER)
- Calculates instantaneous corrosion rate (LPR)
- Rate can be integrated over time for cumulative metal loss
- “Corrosion imbalance” provides qualitative indication of pitting tendency
- Can be tied in with SCADA systems/ 4-20 mA output

# ***PipeSonde In-Pipe Multiple Parameter Probe for Water Distribution Systems***








# ***Gates and Locks – not the complete security solution***



**Number of 55 Gallon Barrels of Material Required to Poison 1 Million Gallons of Water for Some of the Most Dangerous Compounds**







***Tanker trucks are not necessary to Contaminate Water Supplies!***

Measured as Solids


<i>Most Serious Agents</i>	55 Gal drums per 10^6 Gallons Water	General Comments
Aflatoxin	7.6	Potent Carcinogen
Aldicarb	1.1	
Cycloheximide	2.1	
LSD	0.2	Highly Toxic, Psychoactive
Mercuric Chloride	0.2	
Oxamly	5.7	Readily available
Ricin	0.4	
Sodium Cyanide	3.7	Fast acting, readily available
Sodium Fluoroacetate	1.7	Tasteless, Colorless, Odorless
Thallium Nitrate	3.4	
Sarin	1	
VX	0.15	

Liquid

# *Escherichia Coli*





# ***Anthrax - Spores and Vegetative***






# *Giardia duodenalis*





# Integrated System Protection



# ***GuardianBlue Early Warning System***

The First and Only drinking water early warning system certified by the Department of Homeland Security as approved product for homeland security




- Protect Public Health
- Detect and classify events in the distribution system
- Increase security
- Streamline operations



# Approach: Detection by “Fingerprint Signature” of the Toxin

- HACH sensor capable of determining contaminant type from water quality data (TOC, chlorine, pH, etc. as a “generalized vector”).
- Hach sensor is equipped with a library of water quality responses to ~100 classes of agent.



# Beijing Olympics

- GuardianBlue Systems selected for securing drinking water during the recent Beijing Olympic games.







January 19, 2006

"...the operations are under preparation for new attacks and you will see them in your houses as soon as they are complete, God willing."

Osama bin Laden

رئيس تنظيم القاعدة



# ***Methods – Physical Attack***



- Denial of service and collateral damage




**A single terrorist (international, or domestic) can be up and running to attack a water system within days of arrival at target site.**

## **Attack Scenario**

- 12 gallons of readily available toxic substance**
- pump (\$150 rental)**
- wrench to open a fire hydrant (\$10)**
- ***One (1) terrorist, or equivalent, intent upon killing innocent people.***



# ***THE THREAT***







# ***US ARMY\_NAVY CBR CONTAMINATION AND COUNTERMEASURES REPORT***






Figure1. Generalized model out put for an agent injected into a fire hydrant within a 1/2 mile of a targeted building.



# Intrusion 03:00 hours




# Intrusion 03:30 hours







# Intrusion 04:00 hours



# Intrusion 05:00 hours




# Intrusion 06:00 hours







# Intrusion 07:00 hours



# Intrusion 08:00 hours




## Intrusion 09:00 hours







Intrusion 10:00 hours



# Intrusion 11:00 hours




Intrusion 12:00 hours





# ***Backflow Attack Wave front***



## *Results Predicted:*

*In a city of 100,000: Entire Populations Hit with Poisonous Water within 12 hours.  
12% of Population Dead within 48 hours with a 1080 attack; 22% dead with VX  
attack.*

# ***1980 Chlordane Incident***

- Purposeful injection of chlordane into distribution system at an isolated valve location
- System served 10,500, of which 154 reported ill effects
- Continued contamination evident following initial purging resulted in mandated use restrictions
- Ultimately resolved by extended flushing (concentrations reduced from ~1000ug/l to 0.3 ug/l target over 3 months)
- Flushing able to restore usage in 1 month, but 9 months required for potable clearance
- Water heaters particularly difficult to clean



# *The Threat – Current Estimates*

- GAO Report GAO-03-29
- Kroll (Hach HST) “Securing Our Water Supply: Protecting a Vulnerable Resource”
  - ▶ 22 incidents from 2000 to present
  - ▶ 75% of experts (32/43) identify the water distribution system as being most vulnerable (as opposed to source waters or other system components, treatment chemicals, etc.).
- AwwaRF Report
  - ▶ 279 Documented incidents from ~1960’s to 1999
  - ▶ 19 deaths, 166 illnesses confirmed



# ***US Federal Reports on the Backflow Threat:***

US Air Force, *“A Chemical and Biological Warfare Threat---USAF Water Systems at Risk”*, 1999.

GAO, *“Experts Views on How federal Funding Can Best Be Spent to Improve Security”*, 2003.

White House/OSTP, *“The Physical Protection of Critical Infrastructures and Key Assets”*, 2003.

National Research Council, *“Making the Nation Safer”*, 2002

Council of Foreign Relations, *“America Unprepared---America Still in Danger”*, 2002.





# ***THE THREAT-GAO EXPERTS***

- According to report by the General Accounting Office released in 2004
- The *distribution system* is the top vulnerability of drinking water systems with hydrants specifically referenced
- “...the distribution of a chemical, biological or radiological agent via the distribution system could be difficult to detect until it is *too late* to reverse any harm done.”





***Is this scene familiar?***







# ***Antiterrorism Retrofit Valve Internal to Hydrant Barrel***






# Features





# Features

- Meets AWWA C502 Specs
- Offers continuous protection
- Easily retrofitted into new or existing hydrants
- Stealth design
- Fire Fighters operate hydrant as usual
- Ten year warranty
- Extremely durable materials for long life
- Qualifies for funding from several sources



# **AWWA Performance Tests of a Muller Super Centurion 250 Fire Hydrant with a Davidson ATV Security Device**

Written By: William Rahmeyer PhD P.E.

Professor of Engineering, Utah State University


October 2006

prepared for  
Davidson Hydrant Technology Inc.  
Peachtree City, GA.


**Utah Water Research Laboratory**

USU Report 672

**Utah State**  
UNIVERSITY










# Conclusions:

- The Corrosion Program Demonstrations at 2 Army installations are testing an Integrated Water Security Program Dedicated to:
  - (1) Corrosion of Infrastructure: Pipes + Hydrants
  - (2) Protection of Soldiers and Their Families from Water Related Terrorist Attacks




# BACKUP SLIDES





# ***Toxicity of Chemical & Biological Agents***



**Source:** Office of Technology Assessment, *Technologies Underlying Weapons of Mass Destruction* (Washington, D.C.: U.S. Government Printing Office, December 1993), p. 77.



# ***The Threat, CONTINUED***

- Injecting agents into drinking water via fire hydrant
  - ▶ Filling hydrant with agent and siphoning into main
  - ▶ Pumping into hydrant using truck or other tank container as pump

